TEXAS EQUIPMENT

CLEAR FLOOR DIRECT-DRIVED TWO-POST LIFT – 4 Ton MODEL: TEP8009

Description
• Dual hydraulic direct-dived cylinders made on high standard.
• Super Asymmetric arms allow to load different vehicles in an asymmetric or symmetric configuration.
• Aero cable used for synchronization.
• Single-point safety release, allow technician to disengage column simultaneously.
• Self-lubricating UHMW Polyethylene sliders and bronze bush.
• Clear-floor design, provide unobstructed floor use.
• Overhead safety shut-off device prevents vehicle damage.
• Stackable rubber pads and 1.5”,2.5”,5”adapters as standard supply.
• Standard adjustable heights accommodate varying ceiling heights.
• Standard door guards.
• Standard toe guards on lifting arms.

Specifications
Lifting Capacity 4000kg (9,000 lbs)
Lifting Time 57s
Lifting Height A 1815-2044mm (71 1/2″ – 80 1/2″)
Overall Height B 3621/3821mm (142 1/2″ /150 1/2″)
Overall Width C 3428mm (135″)
Drive-Thru Clearance D 2528mm (99 1/2″)
Width Between Columns E 2850mm (112 1/4″)
Minimum Pad Height F 90mm (3 1/2″)
Gross Weight 687kg (1,516 lbs)
Motor 3.0HP/2.0HP
Packing Dimension 2800 X 450 X 825 mm





