



TEXAS EQUIPMENT




Model			
TE4			
Dimensions	Length(mm)	Width(mm)	Height(mm)
Outer Size	7000	5200	3400
Internal Size	6900	3900	2650
Color	Blue and gray		
Features	380V, 50Hz, 3PH		



Detail	Entrance Door				Emergency Door	
	3 Folds Door	3000×2600mm	Sheet metal doors	5mm	2000*650mm	1fold
						


A. Cabin System

Detail	Wall pannel		Basement				
	Rock wool	Galvanized Steel	Plate Type Pressing Convex Platform	Surrounding Edge	Steel Grills	Full Ramps	
	50mm	0.4mm	280 mm	1 Set	2 row 30*5mm	620*2000mm	2pcs
							

B. Ventilation System (can be placed in any position)

Detail	Inlet Fan	Outlet Fan	Rock Wool Fan Cabine	Air Duct	Elbow
	2*4kw	1*7.5kw	1 Set	910 mm *2 pieces	90° *1uni
					

C. Heating System

	Burner	Air Damper	Heat Exchanger				
			Material	Thickness	Baking Temperature Max	Heating from 20 °C to 60 °C	Cabinet
	RIELLO G20	air damper	SUS304 Stainless Steel	1.5mm	80 °C	8-10 minutes	Rock-wool insulation*1 unit
Detail							

D. Roof system

	Beam		Plenum	
	Galvanized Square Pipe		Roof Filter Support Frame	
				

E. Lightening System

	Ceiling Lights			Side Lights	
	Material	Quantity	Total Power	Quantity	Total Power
	LED	8*4 PCS	5.12KW	8*4 PCS	5.12KW
					

F. Filtering System

	Primary filter (In the fan cabinet)		Ceiling filter	Floor filter
	Grade G2 plate typr, filter rate > 83%.		EU5 grade high efficient filter, filtering rate> 98%.	Muliti-layer fiberglass filtering rate>70%
				

G. Control System

Detail			Micro computer controlling system, Lighting, painting, over load, open phase protection.
Total power	16KW		